

TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371

ATTORNEY'S DOCKET NUMBER
13479-002001

U.S. APPLICATION NO. (If Known, see 37 CFR 1.5)

09/936092

INTERNATIONAL APPLICATION NO.
PCT/CN00/00039

INTERNATIONAL FILING DATE
1 March 2000

PRIORITY DATE CLAIMED
9 March 1999

TITLE OF INVENTION
MULTI-POLE ELECTRIC MACHINE

APPLICANT(S) FOR DO/EO/US
Xiabin Bai, Xueming Qiu, Jinghui Bai and

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This is an express request to promptly begin national examination procedures (35 U.S.C. 371(f)).
4. ☐ The US has been elected by the expiration of 19 months from the priority date (PCT Article 31).
5. ☐ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is attached hereto (required only if not communicated by the International Bureau).
 - b. ☐ has been communicated by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
 - b. ☐ have been communicated by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ An English language translation of amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☒ An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11 to 16 below concern other documents or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A FIRST preliminary amendment.
☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☐ Other items or information:



CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EL696752558US

I hereby certify under 37 CFR §1.10 that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Commissioner for Patents, Washington, D.C. 20231.

Sept. 7, 2001

Date of Deposit

Signature

Samantha Bell

Typed Name of
Person Signing

Samantha Bell

U.S. APPLICATION NO. (IF KNOWN)

09/936092

INTERNATIONAL APPLICATION NO.
PCT/CN00/00039ATTORNEY'S DOCKET NUMBER
13479-00200117. ☒ The following fees are submitted:**Basic National Fee (37 CFR 1.492(a)(1)-(5)):**

Neither international preliminary examination fee (37 CFR 1.482)
nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO
and International Search Report not prepared by the EPO or JPO..... **\$1000**

International preliminary examination fee (37 CFR 1.482) not paid to
USPTO but International Search Report prepared by the EPO or JPO **\$860**

International preliminary examination fee (37 CFR 1.482) not paid to USPTO but
international search fee (37 CFR 1.445(a)(2)) paid to USPTO..... **\$710**

International preliminary examination fee paid to USPTO (37 CFR 1.482)
but all claims did not satisfy provisions of PCT Article 33(1)-(4)..... **\$690**

International preliminary examination fee paid to USPTO (37 CFR 1.482)
and all claims satisfied provisions of PCT Article 33(1)-(4)..... **\$100**

ENTER APPROPRIATE BASIC FEE AMOUNT =

\$860.00

Surcharge of **\$130** for furnishing the oath or declaration later than ☐ 20 ☐ 30
months from the earliest claimed priority date (37 CFR 1.492(e)).

\$0.00

Claims	Number Filed	Number Extra	Rate
Total Claims	17 - 20 =	0	x \$18
Independent Claims	3 - 3 =	0	x \$80
MULTIPLE DEPENDENT CLAIMS(S) (if applicable)			+ \$270
TOTAL OF ABOVE CALCULATIONS =			\$860.00

\$0.00

\$0.00

\$0.00

\$860.00

☐ Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are
reduced by 1/2.

\$0.00

SUBTOTAL =

\$860.00

Processing fee of **\$130** for furnishing the English Translation later than ☐ 20 ☐ 30
months from the earliest claimed priority date (37 CFR 1.492(f)).

\$0.00

TOTAL NATIONAL FEE =

\$860.00

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be
accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). **\$40.00** per property +

\$0.00

TOTAL FEES ENCLOSED =

\$860.00

Amount to be
refunded: \$

Charged: \$

a. ☒ A check in the amount of \$860.00 to cover the above fees is enclosed.b. ☐ Please charge my Deposit Account No. 06-1050 in the amount of \$0.00 to cover the above fees. A duplicate copy of this sheet is enclosed.c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 06-1050. A duplicate copy of this sheet is enclosed.

**NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive
(37 CFR 1.137(a) or (b) must be filed and granted to restore the application to pending status.**

SEND ALL CORRESPONDENCE TO:

Y. Rocky Tsao
FISH & RICHARDSON P.C.
225 Franklin Street
Boston, Massachusetts 02110-2804
(617) 542-5070 phone
(617) 542-8906 facsimile

SIGNATURE:

Y. Rocky Tsao

Y. Rocky Tsao

NAME

34,053

REGISTRATION NUMBER

09/936092

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Xiabin Bai et al.
Serial No. : Unassigned
Filed : Herewith
Title : MULTI-POLE ELECTRIC MACHINE

BOX PCT

Commissioner for Patents
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Prior to examination, please amend the application as follows:

In the claims:

Amend claims 2-11 and 13 -14 as follows:

--2. (Amended) The multiple-pole electric machine as claimed in Claim 1, wherein said armature winding is a wave winding without being lapped at the extension.--

--3. (Amended) The multiple-pole electric machine as claimed in Claim 1, wherein said armature winding is a wave winding being partially lapped at the extension.--

--4. (Amended) The multiple-pole electric machine as claimed in Claim 1, wherein said armature winding is a pole-pitch wave winding.--

--5. (Amended) The multiple-pole electric machine as claimed in Claim 1, wherein said armature winding is located in the slot with a single strand of the wires in each layer and both two sides of the wires contact the wall of the iron core.--

CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EL6967525558US

I hereby certify under 37 CFR §1.10 that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Commissioner for Patents, Washington, D.C. 20231.

Date of Deposit

September 7, 2001

Signature

Samantha Bell
Samantha Bell

Typed or Printed Name of Person Signing Certificate

--6. (Amended) The multiple-pole electric machine as claimed in Claim 1, wherein said armature winding is located in the slot with double-strand of the wires in each layer and one of the left side and the right side of the wires contacts the wall of the iron core.--

--7. (Amended) The multiple-pole electric machine as claimed in Claim 2, wherein each pole has m slots; a phase winding is resulted by m windings on each layer; and said m windings are arranged to cross m adjacent slots in the same direction and not being lapped at the extension; the different phase windings can be obtained by translating said m windings on different layers.--

--8. (Amended) The multiple-pole electric machine as claimed in Claim 3, wherein said number of slots belonging to each pole of the iron core is $m \times k$, where m is the number of phase and k is the number of slot occupied by one phase belt; each phase winding comprises k windings, said k windings are arranged to cross k slots from one extension in the same direction, to cross one pole span without being lapped at the other extension, and to come back to the original extension from another k slots there they are not lapped; and all m phase windings on each layer may be obtained by translating said phase winding comprising k windings by $n \times k$ slots, where n is an integer.--

--9. (Amended) The multiple-pole electric machine as claimed in Claim 4, wherein each pole comprises m slots; m phase windings are formed on each layer by m windings and are overlapped each other at the extension; and each phase winding is formed by a pole-pitch wave winding.--

--10. (Amended) The multiple-pole electric machine as claimed in Claim 1, wherein said rotor is of electric exciting; the slot of the iron core are straight; each pole occupies one slot; and said winding is a pole-pitch wave winding wound by a single strand or a double-strand of solid wires and is not lapped at the extension.--

--11. (Amended) The multiple-pole electric machine as claimed in Claim 1, wherein there is an inclination g between the p-m pole of the rotor and the tooth slot of the stator, and the length of the iron core L is met: $L \sin(g) \leq 2T$, where T is the tooth pitch, g is an inclined angle.--

--13. (Amended) The multiple-pole electric machine as claimed in Claim 12, wherein said armature winding is a surface wave winding without being lapped at the extension, and comprises k strands of wires in a single phase winding, wherein said k strands of wires are arranged side by side in the same vertical direction to transversely cross the surface of the iron core from the lower extension to the upper extension without being lapped with each other, and to come back to the lower extension from crossing vertically the surface of the iron core after passing through a pole span at the upper extension, without being lapped; and said k strands of wires are arranged side by side on the surface into a single layer and occupies a width of a phase belt of a phase winding.--

--14. (Amended) The multiple-pole electric machine as claimed in Claim 12, wherein said armature winding is a surface wave winding being partially lapped, and has m phase windings, each of which is a surface wave winding comprising k strands of wires without being lapped at the extension; and said m phase windings are obtained by translating said surface wave winding with k strands of wires and are lapped each other at the extension.—

Remarks

The present application claims priority from Chinese Application 99103828.2 through International Patent Application PCT/CN00/00039.

Applicants have amended the dependency of claims 2-11 and 13-14 to preclude a rejection under 35 U.S.C. 112, fifth paragraph, which provides in part that “ (a) multiple dependent claim shall not serve as a basis for any other multiple dependent claim.” No new matter has been added by the above amendments.

Claims 1-17 are now pending. Prompt examination of the present application, as amended, is respectfully requested.

Attached is a marked-up version of the changes being made by the current amendment.

Applicant asks that all claims be examined. Enclosed is a Enter \$ amount check for excess claim fees and a Enter \$ amount check for the Petition for Extension of Time fee. Please apply any other charges or credits to Deposit Account No. 06-1050.

Respectfully submitted,

Date: 9-7-01

Y. Rocky Tsao
Y. Rocky Tsao
Reg. No. 34,053

Fish & Richardson P.C.
225 Franklin Street
Boston, Massachusetts 02110-2804
Telephone: (617) 542-5070
Facsimile: (617) 542-8906

Version with markings to show changes made

In the claims:

Claims 2-11, 13, and 14 have been amended as follows:

2. (Amended) The multiple-pole electric machine as claimed [as] in Claim 1, wherein said armature winding is a wave winding without being lapped at the extension.
3. (Amended) The multiple-pole electric machine as claimed [as] in Claim 1, wherein said armature winding is a wave winding being partially lapped at the extension.
4. (Amended) The multiple-pole electric machine as claimed [as] in Claim 1, wherein said armature winding is a pole-pitch wave winding.
5. (Amended) The multiple-pole electric machine as claimed [as Claim 1, or 2, or 3 or 4] in Claim 1, wherein said armature winding is located in the slot with a single strand of the wires in each layer and both two sides of the wires contact the wall of the iron core.
6. (Amended) The multiple-pole electric machine as claimed [as Claim 1, 2, 3, or 4] in Claim 1, wherein said armature winding is located in the slot with double-strand of the wires in each layer and one of the left side and the right side of the wires contacts the wall of the iron core.
7. (Amended) The multiple-pole electric machine as claimed [as] in Claim 2, wherein each pole has m slots; a phase winding is resulted by m windings on each layer; and said m windings are arranged to cross m adjacent slots in the same direction and not being lapped at the extension; the different phase windings can be obtained by translating said m windings on different layers.

8. (Amended) The multiple-pole electric machine as claimed [as] in Claim 3, wherein said number of slots belonging to each pole of the iron core is $m \times k$, where m is the number of phase and k is the number of slot occupied by one phase belt; each phase winding comprises k windings, said k windings are arranged to cross k slots from one extension in the same direction, to cross one pole span without being lapped at the other extension, and to come back to the original extension from another k slots there they are not lapped; and all m phase windings on each layer may be obtained by translating said phase winding comprising k windings by $n \times k$ slots, where n is an integer.

9. (Amended) The multiple-pole electric machine as claimed [as] in Claim 4, wherein each pole comprises m slots; m phase windings are formed on each layer by m windings and are overlapped each other at the extension; and each phase winding is formed by a pole-pitch wave winding.

10. (Amended) The multiple-pole electric machine as claimed [as] in Claim 1, wherein said rotor is of electric exciting; the slot of the iron core are straight; each pole occupies one slot; and said winding is a pole-pitch wave winding wound by a single strand or a double-strand of solid wires and is not lapped at the extension.

11. (Amended) The multiple-pole electric machine as claimed [as] in Claim 1, wherein there is an inclination g between the p - m pole of the rotor and the tooth slot of the stator, and the length of the iron core L is met: $L \times \tan(g) \leq 2T$, where T is the tooth pitch, g is an inclined angle.

13. (Amended) The multiple-pole electric machine as claimed [as] in Claim 12, wherein said armature winding is a surface wave winding without being lapped at the extension, and comprises k strands of wires in a single phase winding, wherein said k strands of wires are arranged side by side in the same vertical direction to transversely cross the surface of the iron core from the lower extension to the upper extension without being lapped with each other, and

to come back to the lower extension from crossing vertically the surface of the iron core after passing through a pole span at the upper extension, without being lapped; and said k strands of wires are arranged side by side on the surface into a single layer and occupies a width of a phase belt of a phase winding.

14. (Amended) The multiple-pole electric machine as claimed [as] in Claim 12, wherein said armature winding is a surface wave winding being partially lapped, and has m phase windings, each of which is a surface wave winding comprising k strands of wires without being lapped at the extension; and said m phase windings are obtained by translating said surface wave winding with k strands of wires and are lapped each other at the extension.

FILED

10/pts

Multiple-Pole Electric Machine

Field of the Invention

5 The present invention relates to an improved electric machine with a medium frequency and a low speed, particularly to a multiple-pole electric machine.

Background of the Invention

10 In general, there are two kinds of medium frequency electric machines in prior art: one is of an inductor in which a higher harmonic is induced under a DC excitation; and the other is of a claw pole. The disadvantages of the former are a larger size, a higher cost and a lower efficiency due to utilizing its harmonic field. The disadvantages of the latter are: although it has more poles, the loss of power is too much under a higher frequency due to its longer magnetic circuit of the claw-pole structure. In addition, 15 electric machines in the prior art are of less number of slots due to few poles. Moreover, also to avoid the performances deteriorating due to induction leakage, the slot cannot be too deep for obtaining a higher magnetic potential, and a structure of non-straight slots which has a narrower opening and a wider interior is often used to accommodate more turns of windings. The disadvantages of this structure are that: the increasing of the 20 temperature is limited to result in the output lower, because some turns in each slot must be located at the center of the slot and can't contact the wall of the iron core. Thus the heat dissipation of this windings has to pass through a longer path of the insulating medium until reaching the iron core which plays a strong role of heat dissipation.

25 To overcome the above drawbacks in the prior art, the present invention is to provide a novel electric machine of a medium frequency, particularly an electric machine with more poles.

Summary of the Invention

30 An object of the present invention is to project a multiple-pole electric machine comprising a rotor and a stator, the rotor being of permanent magnet, or of electric excitation, or of induction, the number of poles in the rotor being 8 or more than 8, a

plurality of wave windings being arranged in a plurality of slots correspondingly, and each turn of the windings contacting the wall of the iron core of the stator. wherein the wave windings are formed by wires in the form of layers between which is an equal pitch or an unequal pitch;

5 Another object of the present invention is to provide a multiple-pole electric machine comprising a rotor and a stator, the number of poles in the rotor being 8 or more than 8, the armature core of the stator being slotless, and a winding which is a surface wave winding being arranged on the surface of the armature core in a single layer with an equal pitch or a unequal pitch.

10 Still another object of the present invention is to provide a process for pulse exciting in a permanent magnet electric machine, comprising: a. setting a one or more phase windings in the armature of stator as exciting windings, wherein each exciting winding is provided with a charging circuit and discharging circuit for exciting; b. providing a trigger discharging circuit to each discharging circuit for rendering the
15 triggering of the trigger discharging circuit to occur at a time the winding is facing a magnetic pole within a phase angle of 30° .

20 Compared with the prior art, the electric machine according to the present invention is of the advantages of saving materials, a larger output and a higher efficiency, and a simple process for forming a winding. Moreover, the invention can also be used in other fields in addition to medium frequency machines.

Brief Description of the Drawings

25 Fig. 1 is a sectional view of partial armature core laminations of a slotted stator and windings according to the present invention, in which the winding is of a double- strand in a layer;

Fig. 2 is a sectional view of partial armature core laminations of a slotted stator and windings according to the present invention, in which the winding is of a single strand in a layer;

30 Fig. 3 is a developed view of an inclined structure between poles of a rotor and slots of a stator of a slotted multiple-pole p-m machine according to the present invention;

Fig. 4a is a developed view of a winding not lapped at the extension according to the invention, in which there are 2 phases (m);

Fig. 4b is a vector graph of a current in the winding shown in Fig.4a;

Fig. 5 is a developed view of a pole-pitch wave winding of the present invention, in which the number of phases, m is 3;

Fig. 6 is another developed view of a pole-pitch wave winding of the present invention, in which the number of phase, m is 3;

Fig. 7 is a developed view of a wave winding partially lapped according to the present invention, in which m is 3 and k is 2;

Fig. 8 is a schematic sectional view of a portion of armature core laminations of the non-slotted stator and windings of the present invention;

Fig. 9 is a developed view of a surface wave winding not lapped at the extension according to the present invention;

Fig.10 is a developed view of a pole-pitch winding formed by a single strand according to the present invention, in which m is 2;

Fig. 11 is a view of a p-m rotor magnetized in the radial direction according to the present invention;

Fig. 12 is a vector graph of an exciting current and a potential of the armature of a synchronous electric machine according to the present invention;

Fig. 13 is a graph of a primary waveform of a potential of the armature of a synchronous electric machine according to the present invention;

Fig. 14 is a circuit diagram showing a reference direction of the current of the armature of a synchronous generator according to the present invention;

Fig. 15 is a circuit diagram of a pulse exciting in a synchronous p-m electric machine according to the present invention;

Fig. 16 is a graph showing a relationship between the discharging time of the exciting pulse and a phase voltage according to the present invention;

Fig.17 is a graph showing pulse parameters of a pulsing current for exciting according to the present invention;

Fig. 18 is a graph showing the reference time of a pulse discharging for exciting under three phases according to the present invention;

Fig. 19 shows an embodiment of a circuit for a pulse exciting according to the present invention; and

Fig. 20 is a structure view of an electric exciting rotor of a multiple -pole machine according to the present invention.

5

Detailed Description of the Invention

The present invention will be described in detail in conjunction with the accompanying drawings.

One embodiment of a multiple-pole electric machine according to the present invention comprises a rotor and a stator which is slotted. In this embodiment, armature core laminations of the stator and an arrangement of windings in the slot are shown in Fig. 1 and Fig. 2. As shown in the Figs, slots 101 or 201 occupied by windings is straight with an opening. The armature core lamination of the stator has a tooth portion 103 or 203 and a yoke portion 104 or 204. The sections of the windings in Fig.1 and Fig. 2 are indicated by 102 and 202, respectively. As shown in Fig. 1, there are 6 layers of the windings in each slot and each layer comprises double-strand windings consisting of solid wires. As shown in Fig. 2, there are 4 layers of the windings in each slot and each layer comprises one-strand windings consisting of solid wire. From Fig.1 and 2, wires in each turn of the windings except for an insulating layer directly adjoins the wall of the armature core so as to improve the performance of a temperature change. In the case of the double-strand windings, a wedge can be provided at the opening of the slot to decrease loss of power. The rotor used in the embodiment may be a p-m one, an electric excitation one, or of an induction one.

The armature winding is formed under a principle that it is winded in different layers and to keep the portion of the extension as short as possible. Thus, the winding is formed as a wave winding with an equal pitch or an unequal pitch. The winding used in the invention comprises a wave winding without lapping at the extension; a pole-pitch wave winding; and a wave winding with an overlapping.

In the first kind of a wave winding, each pole comprises m slots. Chinese patent 94116888.1 has disclosed such a winding in which m is 3. In the present invention, m may be an integer. Fig.4a shows a developed view of a winding on a layer in a straight

slot in which m is 2. In this case, m sets of the windings for m phases are arranged into m adjacent slots in the same direction without being lapped at the extension. 407 represents a pole of the rotor, and 408 is a tooth of the stator. Each pair of poles corresponds 4 slots of the stator. The electric angle between two adjacent slots is 90° .

5 Windings 401 and 402 ($m=2$) located in the same layer are arranged to be over the first adjacent two slots in the same direction from the downside to the upperside, not lapped at the upper extensions, and then arranged into the adjacent third and fourth slots in the same direction from the upperside back to the downside without being lapped each other. 403, 404, 405, and 406 respectively represents current directions in the winding
10 in the adjacent four slots at a time. Their vectors are shown in Fig. 4b, in which vectors 413 and 414 correspond to currents 403 and 404 in the same winding 401 as shown in Fig. 4a, and their resultant vector is J . Vectors 415 and 416 respectively correspond to currents 405 and 406 in the same winding 402 as shown in Fig.4a, and their resultant vector is also J . By selecting the polarities, windings 401 and 402 may be arranged in
15 series or in parallel to obtain a resultant phase winding with a phase vector in the direction J , which represents a vector of the winding on this layer. Four phase windings respectively having phases 0° , 90° , 180° , and 270° can be obtained by translating a phase winding in a layer a slot four times. In particular, by translating a pole span a phase winding having a phase-shift of 180° is obtained.

20 The second kind of a wave winding is a pole-pitch wave winding. Each pole comprises m slots, where m is the number of phase. Figs 5 and 6 show two kinds of such windings in which m is 3. Each of windings 501, 502 and 503 in Fig. 5 for three phases has a pitch equal to a pole span. A developed plan of a tooth of the slot is indicated as 504. The three windings 501, 502 and 503 located at the same layer are
25 lapped with each other at the extension. Thus, there is a sufficient space left at the extension to wind wires. Similar to Fig. 5, in Fig. 6, a developed plan 604 correspond to the developed plan 504 in Fig. 5, and windings 601 and 602 correspond to the windings 502 and 503, respectively. A winding 603 is formed by translating winding 503 in Fig. 5 a pole span (three slots). Therefore, the winding 603 has a reverse phase to the windings
30 503.

The third kind of a wave winding is a partially lapping winding. Such a wave

winding has partial features of both above two kinds of windings. The winding in one phase is arranged without being lapped at the extension and is of a phase belt and more than 0° . Another phase winding can be formed by translating a phase winding onto another phase band. Phase windings at the same layer are lapped at the extension, as shown in Fig. 7. In Fig. 7, there are three phases (m is 3). The phase belt of each phase occupies 2 slots. In this case, each pole comprises $m \times k = 3 \times 2 = 6$ slots. The width of the phase belt is that of 1 slot ($k-1$), i.e. its electric angle is 30° . As a result, the harmonic performance is improved. The developed plans of two teeth between which there is a span occupied by a pair of poles are indicated as 707 and 708, respectively. Windings 701 and 702 constitute a phase winding which is wound in a way similar to that shown in Fig. 4a. That is, they are arranged to cross two adjacent slots in the same direction without being lapped at the extension. In this case, however, the number of the slots crossed is more than that in Fig. 4a although a pole span has been crossed. The windings 703 and 704 for the next or second phase can be obtained by translating the windings 701 and 702 two slots. Similarly, windings 705 and 706 for the third phase can be obtained. Similar to that in Fig. 6, the three sets of the windings for the three phases are lapped at the extension. Alternatively, they may be arranged according to the manner shown in Fig. 5. The skilled in the art should appreciate the case when m and k are any other integer.

The above three kinds of wave windings arranged in different layers including windings 401 and 402 in Fig. 4a, windings 501, 502, and 503 in Fig. 5, windings 601, 602, and 603 in Fig. 6, and windings 701 through 706 in Fig. 7 are described for those arranged with a stand or double-stand wire in layers in a slot, which are shown as 202 in Fig. 2 and 102 in Fig. 1.

The above arrangements of the windings are simple and are easily automated and may reach an optimal design to make the length at the extension minimal, thereby saving copper, decreasing induction leakage, and improving the performance of medium and high frequency. Also, all the wires of the windings contact the wall of the iron core to create a better heat dissipation and a higher output.

It should be appreciated that the teeth in Figs 4a, 5, 6 and 7 have a rectangular contour, the developed plan 408 as shown in Fig. 4a is rectangular, and the developed

plan of the tile-like pole 407 of the rotor is also rectangular. This structure between the rotor pole and the stator slot is called as a straight one. In addition, in case the rotor is of a permanent magnet, an inclined structure between the pole of the rotor and the slot is formed, as shown in Fig. 3. The inclined structure may also be formed using the iron core with straight slots as shown in Fig.1 and Fig. 2. In Fig. 3, the developed plan of magnetic poles N and S of the rotor is rectangular, and has its axis 303. A developed plan 301 of the tooth is a parallelogram. The axis of the tooth is indicated as 304. The slot 302 is inclined. The inclination between the axis 303 and the axis 304 is indicated as an angle g . The length of the iron core is L , and the tooth span is T . It is noted that with this structure an improved wave shape may be obtained to decrease the electric-magnetic loss. Also, the key points of this structure lies in that the angle g is not 0. That is, the structure may be formed in a way that the slot of the tooth is rectangular, the developed plan of the pole of the rotor is a parallelogram and an angle between the axis of the pole and the axis of the tooth is kept g . A better harmonic performance can be obtained with the above two inclined structures.

According to the present invention, the optimal angle g should meet that: $L \times \tan(g)$ is not more than $2T$.

Another embodiment of the present invention is a non-slotted multiple-pole electric machine. Its rotor is of permanent magnet and its iron core of the stator is non-slotted, as shown in Fig. 8. A magnetic yoke 801 consisting of a non-slotted lamination, and a wire section 802 of a winding are shown in Fig. 8. Although the wire section 802 is circular in the Fig, it should be understood that the wire having a flat section may have a better effect. The wire of the winding is attached to the surface of the iron core adjacent to the air gap. The arrangement of the winding follows a principle that each turn of the wire of the winding contacts the iron core and makes its extension portion as short as possible. This arrangement refers to as a surface wave winding with an equal or unequal pitch in a single layer. Also, three kinds of windings are provided: the first is a surface wave winding without being lapped at the extension; the second is a surface pole-pitch wave winding; the third is a surface wave winding with being partially lapped at the extension.

The above surface wave winding without being lapped at the extension is shown in

Fig. 9, which shows a schematic developed view formed by developing the plan of a cylindrical air gap of the iron core along the circumference. Reference numeral 904 represents a portion of the iron core cylinder surface at the side of the air gap, L is the length of the iron core, and poles N and S of the rotor are indicated as 905. The pole span of a pair of poles is 2τ . Windings 901, 902 and 903 show the arrangement of the surface wave windings without being lapped at the extension in the case of $k = 3$. The windings 901, 902 and 903 cross the surface of the iron core vertically in the same direction and occupy a width of B on the surface (the width of a phase belt). A winding for a phase is formed by connecting windings 901, 902 and 903 in series.

A pole-pitch wave winding formed by a single strand is shown in Fig. 10, in which m is 2. The developed plan of the iron core is indicated as 1003. The length of the iron core is L . Windings 1001 and 1002 are formed with a respective single strand in the same manner for two phases. One of them can be obtained by translating the other one a half of a pole span (a phase shift of 90°). The windings 1001 and 1002 are lapped on points 1004 and 1005 at the extension. As shown in Fig. 10, the winding 1001 is above the winding 1002 and lapped therewith at the point 1004, while the winding 1002 is above the winding 1001 at the point 1005 and lapped therewith. The position of the windings 1001 and 1002 can be changed each other. The pole span of magnetic poles N and S of the rotor is τ . The disadvantage of the winding formed by a single strand is that the application ratio of the surface is lower. To increase the application ratio of the surface, it is recommended to use a method in combination of that shown in Fig. 9 with that shown in Fig. 10 in which the winding is partially lapped at the extension. Thus, windings 901, 902 and 903 for a phase as shown in Fig. 9 as a phase winding replaces each of windings 1001 and 1002 for two phases in Fig. 10 to form a surface winding including 2 phases ($m=2$), each phase comprising 3 strands of wires ($k=3$), and the width of the phase belt being B . This surface winding is characterized in that: k strands of the winding for each phase are not lapped at the extension, but lapped between the windings with a different phase at the extension. Those skilled in the art should understand the case when m or k is any integer.

The advantages of this structure are that: the manufacture of the iron core is simple and the materials are saved because it is non-slotted; and the waveform is better, the

noise is lower and the operation is silent and smooth because there is no effect of teeth and slots.

When the rotor is of permanent magnet as shown in Fig. 11, a radial air gap may be incorporated in the magnetic circuit. In Fig. 11, the rotor is provided with tile-like permanent magnets 1101. The yoke of the rotor iron core is shown as 1103, and the direction of the magnetic flux is shown by an arrow 1102.

Alternatively, the structure of the magnetic circuit may be axial. In this case, the structure of the electric machine is a disk type. Also, other usable magnetic pole structures in the prior art can be selected.

According to the present invention, there is provided a method for enhancing the exciting of a multiple-pole p-m electric machine of medium frequency, i.e. a method of pulse exciting. The method can be used to increase power of the above p-m electric machine. The method comprises the following steps of:

- a. providing one excitation winding or more excitation windings on the armature, windings for a phase or for all m phases of the armature being preferably used as excitation windings; and
- b. applying a pulsing current to each excitation winding at a time when a p-m pole of the rotor is coming in each cycle of the current to generate a pulsing magnetic field induced which enhances the field of the rotor, i.e. the permanent magnet being magnetized instantaneously by the pulse current to lead the flux in the air gap to rise that thanks to the effects of magnetic reluctance and resistance, so that the induced potential is increased.

The present invention will be described in detail with reference to a generator.

It has been well known that the phase F of the magnetic potential of exciting in a synchronous generator leads the potential E_o of the armature by 90° , as shown in Fig.12. A winding for a phase is of a waveform of the potential E_a as shown in Fig. 13. In Fig. 13, the potential reaches its positive peak at a time of T_2 and reaches its negative peak at time T_4 , which means that the winding is exactly facing N pole of the rotor at T_1 , a time of zero passage, and exactly facing S pole of the rotor at T_3 , another time of zero passage. In the case of a p-m synchronous generator, when a winding W_a of a phase as shown in Fig.14 with a waveform of potential E_a shown in Fig. 13, whose positive

current is taken as a reference direction, is applied with an advanced positive exciting pulsing current I_p through an exciting circuit 1401 at a time of T_1 , i.e. 90° before the positive peak, as shown in Fig. 14, a flux in the direction of its permanent magnet pole is increased to thereby enhance the excitation. In the same way, a negative pulsing current $-I_p$ may be applied to the winding W_a shown in Fig.14 at a time of T_3 in Fig. 13, i.e. 90° after the positive peak, to enhance the excitation.

Fig.15 shows a circuit to implement the process for the pulse exciting to a multiple-pole p-m synchronous machine according to the present invention. In the Fig, 1501 is a winding for a phase, and includes a neutral point G, a terminal H whose phase potential is E_a and a tap M connected to the circuit. In general, M is coincided with H, i.e. no tap M. The exciting circuit comprises a discharging switch 1502, such as a thyristor, with a control terminal 1503, a capacitor 1504 for charging and discharging, a DC power device 1505 for charging, generally such as a rectification circuit for the phase voltage of the generator itself, and a buffer device 1506 for charging and discharging, such as a resistance or an insulating switch. The direction of the current during the charging is indicated by an arrow 1507.

Fig. 16 shows the primary wave of the phase potential E_a during the p-m generator with a pulse exciting circuit shown in Fig.15 being actuated. When t is T_3 , the phase angle θ is 0. θ_1 and θ_2 are a phase angle at a time before and after T_3 , respectively, and their maximum of the absolute value are 30° . Fig.17 schematically shows the waveform of the pulsation current with a starting time T_s .

Refer to Figs 15, 16, and 17. When the control terminal 1503 in Fig. 15 is triggered at a time between θ_1 and θ_2 in Fig. 16 and Fig. 17, such as at T_s in Fig. 17, to make the charging switch 1502 on, the current 1507 has a pulse 1701 as shown Fig.17, whose width D , i.e. the phase difference between the time of T_s and a time when the waveform of the current drops to 10% of the peak, is not less 60 degrees.

In the case of a normal three-phase machine, all the three sets of windings for the three phases may be provided with the above exciting means. As a result, the phase potential can be increased by 30% by applying a respective exciting pulse to each cycle.

The direction of the exciting current in Fig. 15 can be reversed if the polarities in the related devices are reversed, and the starting time of T_s should be changed to around

T1.

Using different methods, the reference phase position θ and the reference time T3 for discharging can be tested to determine the starting time Ts.

One method in the prior art is phase position testing, in which the time of the peak or the zero passage of the phase voltage is tested, and a suitable Ts between θ_1 and θ_2 is obtained by means of a delay circuit.

Another method is using a position sensor. In this method, the position sensor, such as a Hall element, is embedded in a suitable position of the winding of the armature of the stator to test the coming time of the magnetic pole of the rotor. This also is well known in the prior art.

It is appreciated for those skilled in the art that the circuit shown in Fig.15 may also be used to a motor. The reference direction Ia in Fig. 15 is reversed when the motor is in the synchronous state. In this case, as long as the direction of current 1507 in Fig. 15 and the timing in Fig.17 are remained, the conditions of applying the pulse during the time of the pole coming are still met.

An embodiment of the method of enhancing the excitation for a p-m synchronous generator of three phases according to the present invention will be described below.

For the purpose of explanation, in this embodiment, the pole of the p-m synchronous generator is the same as shown in Fig. 11, the iron core of the stator is the same as shown in Fig. 1 or Fig. 2, and the winding may be any kind of the above wave windings with an equal or unequal pitch. The three windings for the three phases are in a sequence of a→b→c like the conventional. Fig. 18 shows the waveform of the voltages for a, b-phase with the phase voltage of a-phase leading that of b-phase by 120°, in which θ is a phase angle and t is a coordinate axle of time. Both points T1 and point T3 are the points of zero passage for the voltage of a-phase. The a- and b- phases have the same potential at 180°. The phase angle of point 180° is the phase difference between the phase position θ_1 and the phase position of point T3, and is exactly equal to 30°. θ_1 is used as a reference phase position, or reference time for discharging to the winding for the a-phase.

A circuit for charging and discharging of the a-phase is shown in Fig. 19. The phase sequence of the generator is a→b→c. In the Figure, G is a neutral point, 1901 is an

output terminal of the voltage for the a-phase, 1902 is a charging and discharging capacitor, 1903 is a charging power, which may generally be an alternating current power for the a-phase or the c-phase, 1904 is a diode of the circuit for charging, 1905 is a current limiting resistance for charging, which also serves as a buffer resistance during
5 discharging, 1906 is a thyristor with a gate 1907, 1908 is a control power taken from the b-phase, 1909 is a diode, resistances 1910 and 1911 form a shunt circuit to adjust the level of the trigger pulse, and resistance 1913 and Zener diode 1914 form a chopper circuit to make the voltage of gate 1907 have a adequate rate of rise. The diode 1914 also serves to protect the gate 1907. To adjust the resistance 1910 or 1911, the delay
10 time from the phase position θ_1 to T_3 in Fig 18, i.e. T_s in Fig. 17 can be finely adjusted.

The circuit for charging and discharging of the other two phase, i.e. b- and c-phases are the same as the above. For example, the related phase positions for the b-phase may be obtained by shifting the respective phase positions in Fig. 18 and Fig. 19 backward by an order of phase. Namely, a-phase, b-phase and c-phase in Fig. 18 and Fig. 19 are
15 changed to b-phase, c-phase and a-phase, respectively.

The advantages of this excitation are of a simple configuration, no electric brush, no change of the mechanical structure, lower power for the excitation, and higher output.

The present invention further provides a rotor structure for the electric excitation
20 for the slotted multiple-pole machine. Fig. 20 shows a developed view of a winding and an iron core of the rotor.

In the medium frequency generator of claw- pole type in prior art, a centered magnetic circuit is formed in the iron core of the rotor to branch the flux to each pair of claw poles. However, in the iron core of the rotor of the present invention shown in Fig.
25 20, the iron core with the magnetic poles N and S consists of iron core lamination 2001. The pole span is τ . As shown in the Figure, the magnetic lines only pass through the adjacent two poles. Each pole corresponds to a slot in which the wires of the winding are winded in one or two strands on each layer according to the arrangement of the pole-pitch wave winding of the present invention. Fig. 20 shows the case of two
30 layers of the winding in each slot and two strands (2002 and 2003 being sections of the wires) in each layer. The direction of outlet and inlet of the current is indicated as \odot

and \otimes , respectively. The developed plan of the stator laminations is indicated as 2004. 2005 is a section of a winding of three layers in the slot. The number of the layer can be changed by adjusting the depth of the slot to obtain proper ampere turns for excitation. This structure has following advantages of a simple winding, good performance of temperature change and high efficiency.

10

15

20

25

30

What is claimed is:

1. A multiple-pole electric machine comprising a rotor and a stator, wherein the rotor is of p-m, of electric excitation, or of induction; the number of poles is 8 or more; armature winding is formed by solid wires and is arranged into layers in a slot to form a wave winding with an equal or unequal pitch; and each turn of said winding in the slot contacts the wall of the iron core of the stator.
2. The multiple-pole electric machine as claimed as Claim 1, wherein said armature winding is a wave winding without being lapped at the extension.
3. The multiple-pole electric machine as claimed as Claim 1, wherein said armature winding is a wave winding being partially lapped at the extension.
4. The multiple-pole electric machine as claimed as Claim 1, wherein said armature winding is a pole-pitch wave winding.
5. The multiple-pole electric machine as claimed as Claim 1, or 2, or 3 or 4, wherein said armature winding is located in the slot with a single strand of the wires in each layer and both two sides of the wires contact the wall of the iron core.
6. The multiple-pole electric machine as claimed as Claim 1, 2, 3, or 4, wherein said armature winding is located in the slot with double-strand of the wires in each layer and one of the left side and the right side of the wires contacts the wall of the iron core.
7. The multiple-pole electric machine as claimed as Claim 2, wherein each pole has m slots; a phase winding is resulted by m windings on each layer; and said m windings are arranged to cross m adjacent slots in the same direction and not being lapped at the extension; the different phase windings can be obtained by translating said m windings on different layers.
8. The multiple-pole electric machine as claimed as Claim 3, wherein said number of slots belonging to each pole of the iron core is $m \times k$, where m is the number of phase and k is the number of slot occupied by one phase belt; each phase winding comprises k windings, said k windings are arranged to cross k slots from one extension in the same direction, to cross one pole span without being lapped at the other extension, and to come back to the original extension from another k slots

where they are not lapped; and all m phase windings on each layer may be obtained by translating said phase winding comprising k windings by $n \times k$ slots, where n is an integer.

9. The multiple-pole electric machine as claimed as Claim 4, wherein each pole comprises m slots; m phase windings are formed on each layer by m windings and are overlapped each other at the extension; and each phase winding is formed by a pole-pitch wave winding.

10. The multiple-pole electric machine as claimed as Claim 1, wherein said rotor is of electric exciting; the slot of the iron core are straight; each pole occupies one slot; and said winding is a pole-pitch wave winding wound by a single strand or a double-strand of solid wires and is not lapped at the extension.

11. The multiple-pole electric machine as claimed as Claim 1, wherein there is an inclination g between the p-m pole of the rotor and the tooth slot of the stator, and the length of the iron core L is met: $L \times \tan(g) \leq 2T$, where T is the tooth pitch, g is an inclined angle.

12. A multiple-pole electric machine comprising a rotor and stator, wherein the number of poles is 8 or more; the iron core of the stator includes no slots; and the armature winding is a surface wave winding with an equal or unequal pitch and is arranged on the surface of the winding in a single layer.

13. The multiple-pole electric machine as claimed as Claim 12, wherein said armature winding is a surface wave winding without being lapped at the extension, and comprises k strands of wires in a single phase winding, wherein said k strands of wires are arranged side by side in the same vertical direction to transversely cross the surface of the iron core from the lower extension to the upper extension without being lapped with each other, and to come back to the lower extension from crossing vertically the surface of the iron core after passing through a pole span at the upper extension, without being lapped; and said k strands of wires are arranged side by side on the surface into a single layer and occupies a width of a phase belt of a phase winding.

14. The multiple-pole electric machine as claimed as Claim 12, wherein said armature winding is a surface wave winding being partially lapped, and has m phase

windings, each of which is a surface wave winding comprising k strands of wires without being lapped at the extension; and said m phase windings are obtained by translating said surface wave winding with k strands of wires and are lapped each other at the extension.

5 15. A method for pulse exciting of a p-m generator having 8 poles or more, comprising the following steps of:

a. setting one or more phase windings on the armature as exciting windings, each exciting winding comprising an exciting circuit for charging and discharging; and

10 b. setting a trigger circuit for discharging in said circuit for discharging so that a trigger take places within 30° before and after said windings are exactly facing a pole.

15 16. The method for pulse exciting of a p-m generator as claimed in Claim 15, wherein said exciting circuit for charging and discharging comprises a capacitor for charging and discharging to perform a process of charging and discharging in a electric cycle, wherein the direction of discharging is that of enhancing the pole; said circuit for charging comprises a rectification circuit and a current-limiting resistance; and said circuit for discharging comprises a switch and a trigger circuit thereof.

20 17. The method for pulse exciting of a p-m generator as claimed in Claim 16, wherein said trigger circuit of said switch comprises a position sensor for testing a pole position or a tester for testing a phase position of a phase voltage, to obtain the information of the time of the pole coming and to produce a trigger signal for discharging.

25

30

Abstract

The present invention relates to an improved structure for an electric machine of medium frequency and low speed, in particular, to a multiple-pole electric machine. The rotor of the multiple pole electric machine of the present invention is of p-m, of electric excitation, or of induction. The number of poles is equal to or more than 8. Solid wires are arranged into layers in the slots to form the wave windings of the armature with an equal or unequal pitch. The windings are located in the slots and each turn of the wires contact the wall of the iron core. Compared with the prior art, the multiple-pole electric machine of this invention saves copper and iron materials, increases output, improves efficiency and makes the manufacturing of the windings easy. It can apply to other case in addition to replacing a conventional medium frequency electric machine.




Figure 1




Figure 2

2/10




Figure 3




Figure 4

3/10




Figure 5




Figure 6

4/10




Figure 7




Figure 8

5/10




Figure 9




Figure 10

6/10




Figure 11




Figure 12

7/10




Figure 13




Figure 14

8/10




Figure 15




Figure 16

9/10




Figure 17




Figure 18

Figure 20

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled Multi-Pole electric machine, the specification of which:

- ☒ is attached hereto.
☐ was filed on _____ as Application Serial No. _____ and was amended on _____.
☐ was described and claimed in PCT International Application No. _____ filed on _____ and as amended under PCT Article 19 on _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose all information I know to be material to patentability in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim the benefit under Title 35, United States Code, §119(e)(1) of any United States provisional application(s) listed below:

U.S. Serial No.	Filing Date	Status
-----------------	-------------	--------

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose all information I know to be material to patentability as defined in Title 37, Code of Federal Regulations, §1.56(a) which became available between the filing date of the prior application and the national or PCT international filing date of this application:

U.S. Serial No.	Filing Date	Status
-----------------	-------------	--------

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

Country	Application No.	Filing Date	Priority Claimed
China	99103828.2	March 9, 1999	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No

I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Combined Declaration and Power of Attorney
Page 2 of 2 Pages

Y. Rocky Tsao, Reg. No. 34,053
Eric L. Pahl, Reg. No. 32,590
Harold H. Fox, Reg. No. 41,498

Frank R. Occhiuti, Reg. No. 35,306
John F. Hayden, Reg. No. 37,640

Address all telephone calls to Y. ROCKY TSAO at telephone number (617) 542-5070.

Address all correspondence to Y. ROCKY TSAO at:

FISH & RICHARDSON P.C.
225 Franklin Street
Boston, MA 02110-2804

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patents issued thereon.

Full Name of First Inventor: Xiabin Bai 白俠文 Date: 8.31.2001
Inventor's Signature: _____
Residence Address: 1st FL., 7th Building, Gaofaxiaoqu, Longjingzhuguang Industrial Zone, Nanshan District, Shenzhen 518055, P.R.China
Citizenship: CNZ Citizen of China
Post Office Address: 1st FL., 7th Building, Gaofaxiaoqu, Longjingzhuguang Industrial Zone, Nanshan District, Shenzhen 518055, P.R.China

Full Name of Second Inventor: Xueming Qiu
Inventor's Signature: Xu Ming Qiu Date: 8.26.2001
Residence Address: 1st FL., 7th Building, Gaofaxiaoqu, Longjingzhuguang Industrial Zone, Nanshan District, Shenzhen 518055, P.R.China
Citizenship: CNZ Citizen of China
Post Office Address: 1st FL., 7th Building, Gaofaxiaoqu, Longjingzhuguang Industrial Zone, Nanshan District, Shenzhen 518055, P.R.China

Full Name of Third Inventor: Jinghui Bai
Inventor's Signature: 白景輝 Date: 8.31.2001
Residence Address: 1st FL., 7th Building, Gaofaxiaoqu, Longjingzhuguang Industrial Zone, Nanshan District, Shenzhen 518055, P.R.China
Citizenship: CNZ Citizen of China
Post Office Address: 1st FL., 7th Building, Gaofaxiaoqu, Longjingzhuguang Industrial Zone, Nanshan District, Shenzhen 518055, P.R.China